

Exhibit B

Final Changes to the Calvert County Zoning Ordinance

Section 1-2.01

1-2 APPLICATION OF THIS ORDINANCE

1-2.01 Territorial Limits

This Ordinance shall apply to all the lands, uses and improvements within the territorial limits of Calvert County, except for the incorporated territory of any municipality in the County, or except as modified by the Town Center Master Plans and Zoning Ordinances. Except as otherwise specified, the use of any property and the construction or alteration of any building or structure shall conform to the requirements of this Ordinance.

1-2.02 Determination of Rights Attendant to a Parcel

For the purpose of determining rights attendant to a parcel of land by virtue of the property being a discrete parcel, any determination as to the description of the parcel shall go back no further than the parcel as it existed in a deed under which the grantee in the deed held title to real property as of June 29, 1967.

1-2.03 Exemption

Notwithstanding any other provisions of this Ordinance to the contrary, this Ordinance does not apply to a Qualified Commercial Power Generating Facility as defined herein.

1-2.04 Statutory Authorization

The Maryland General Assembly, in Article 66B, Section 4, General Development Regulations and Zoning (Annotated Code of Maryland), has established as policy of the State that the orderly development and use of land and structures requires comprehensive regulation through the implementation of planning and zoning control, and that planning and zoning controls shall be implemented by local government in order to, among other purposes, secure the public safety, promote health and general welfare, and promote the conservation of natural resources.

Section 5-1.11

5-1 .11 Height Regulations for All Districts

No building or structure shall exceed 40 feet, including the roof, except as indicated in paragraphs 'A' through 'C' of this Section. The maximum height of a building or structure shall be measured from the average elevation of the finished grade at the front of the building facing the street to the highest point of the roof except as indicated in Section C, below.

- A. Fire towers, hose towers, cooling towers, steeples, flag poles, silos, smokestacks, masts, transmission line poles and towers, water tanks, and monuments are exempt from height restrictions unless used for the purpose of camouflaging or concealing wireless communications facilities such as towers or antennas. Towers, antennas and wind energy systems (i.e., windmills) shall be subject to the requirements of Section 3-3 herein.
- B. A clock tower or cupola containing no more than 150 square feet may exceed the height regulations by no more than 12 feet.
- C. For structures with the lowest floor support beams raised to or above the flood protection elevation, the maximum height of a building or structure shall be measured from the flood protection elevation to the highest point of the roof. For structures with the lowest floor support beams raised to one foot above the flood protection elevation, the maximum height of a building or structure shall be measured from the flood protection elevation plus one foot to the highest point of the roof.

Section 8-2.03

8-2.03 Floodplain Area

A. Background

- 1. The Federal Emergency Management Agency has identified *special flood hazard areas* within the boundaries of Calvert County. *Special flood hazard areas* are subject to periodic inundation which may result in loss of life and property, health and safety hazards, disruption of commerce and governmental services, extraordinary public expenditures for flood protection and relief, and impairment of the tax base, all of which adversely affect the public health, safety and general welfare. *Structures* that are inadequately elevated, improperly *floodproofed*, or otherwise unprotected from flood damage also contribute to flood losses.
- 2. Calvert County, by resolution, agreed to meet the requirements of the National Flood Insurance Program and was accepted for participation in the program on September 28, 1984. As of that date

or as of September 28, 1984 the initial effective date of the Calvert County *Flood Insurance Rate Map*, all *development* and *new construction* as defined herein, are to be compliant with these regulations.

B. Purpose

It is the purpose of these regulations to promote the public health, safety and general welfare, and to:

1. Protect human life, health and welfare,
2. Encourage the utilization of appropriate construction practices in order to prevent or minimize flood damage in the future,
3. Minimize *flooding* of water supply and sanitary sewage disposal systems,
4. Maintain natural drainage,
5. Reduce financial burdens imposed on the *community*, its governmental units and its residents, by discouraging unwise design and construction of *development* in areas subject to *flooding*,
6. Minimize the need for rescue and relief efforts associated with *flooding* and generally undertaken at the expense of the general public,
7. Minimize prolonged business interruptions,
8. Minimize damage to public facilities and other utilities such as water and gas mains, electric, telephone and sewer lines, streets and bridges,
9. Reinforce that those who build in and occupy *special flood hazard areas* should assume responsibility for their actions,
10. Minimize the impact of *development* on adjacent properties within and near *flood-prone areas*,
11. Provide that the *flood storage* and conveyance functions of *floodplains* are maintained,
12. Minimize the impact of *development* on the natural and beneficial functions of *floodplains*,
13. Prevent *floodplain* uses that are either hazardous or environmentally incompatible; and
14. Meet community participation requirements of the National Flood Insurance Program as set forth in the Code of Federal Regulations at 44 C.F.R. Section 59.21.

C. Boundaries

These regulations shall apply to all *special flood hazard areas* within the jurisdiction of the Calvert County, and identified below:

1. For the purposes of these regulations, the minimum basis for establishing *special flood hazard areas* and *base flood elevations* is the *Flood Insurance Study* for Calvert County, Maryland and Incorporated Areas dated December 16, 2011, or the most recent revision thereof, and the accompanying *Flood Insurance Rate Maps* and all subsequent amendments and revisions to the *FIRMs*. The *FIS* and *FIRMs* are retained on file and available to the public at the Department of Planning and Zoning.
2. Where field surveyed topography or digital topography indicates that ground elevations are below the closest applicable *base flood elevation*, even in areas not delineated as a special flood hazard on the *FIRM*, the area shall be considered as *special flood hazard area*. Where map boundaries and elevations disagree, elevations prevail, with no approval from FEMA required.
3. To establish *base flood elevations* in *special flood hazard areas* that do not have such elevations shown on the *FIRM*, the Floodplain Administrator may provide the best available data for *base flood elevations*, may require the applicant to obtain available information from Federal, State or other sources, or may require the applicant to establish *special flood hazard areas* and *base flood elevations* as set forth in Section 8-2.03.H.3-5 of these regulations.
4. Land composed of alluvial soils (My soils) on United States Department of Agriculture (USDA) Soil Survey Maps for Calvert County.

D. Abrogation and Greater Restrictions

These regulations are not intended to repeal or abrogate any existing regulations and ordinances, including subdivision regulations, zoning ordinances, *building codes*, or any existing easements, covenants, or deed restrictions. In the event of a conflict between these regulations and any other ordinance or section of this ordinance, the more restrictive shall govern.

In the interpretation and application of these regulations, all provisions shall be:

1. Considered as minimum requirements;

- 2. Liberally construed in favor of the governing body; and,
- 3. Deemed neither to limit nor repeal any other powers granted under State statutes; where a provision of these regulations may be in conflict with a State or Federal law, such State or Federal law shall take precedence.

Notes referencing publications of the Federal Emergency Management Agency refer to the most recent edition of those publications, are intended only as guidance, and do not bind or alter the authority of the Floodplain Administrator to interpret and apply these regulations.

F. Warning and Disclaimer of Liability

- 1. The degree of *flood* protection required by these regulations is considered reasonable for regulatory purposes and is based on scientific and engineering considerations. Larger floods can and will occur, and *flood* heights may be increased by man-made or natural causes. These regulations do not imply that land outside of the *special flood hazard areas* or uses that are permitted within such areas will be free from *flooding* or *flood* damage.
- 2. These regulations shall not create liability on the part of Calvert County, any officer or employee thereof, the Maryland Department of the Environment (MDE) or the Federal Emergency Management Agency (FEMA), for any *flood* damage that results from reliance on these regulations or any administrative decision lawfully made hereunder.

G. Severability

Should any section or provision of these regulations be declared by the courts to be unconstitutional or invalid, such decision shall not affect the validity of the regulations as a whole, or any part thereof other than the part so declared to be unconstitutional or invalid.

H. Administration

1. Designation of the Floodplain Administrator

The Director of the Department of Planning and Zoning shall appoint the Floodplain Administrator. The Floodplain Administrator may:

- a. Delegate duties and responsibilities set forth in these regulations to qualified technical personnel, plan examiners, inspectors, and other employees.

available on such *structures*; areas subject to this limitation are shown on *Flood Insurance Rate Maps* as Coastal Barrier Resource System Areas (CBRS) or Otherwise Protected Areas (OPA).

- g. Approve applications and issue permits to develop in *flood* hazard areas if the provisions of these regulations have been met, or disapprove applications if the provisions of these regulations have not been met.
- h. Inspect or cause to be inspected, buildings, *structures*, and other *development* for which permits have been issued to determine compliance with these regulations or to determine if non-compliance has occurred or *violations* have been committed.
- i. Review *Elevation Certificates* and require incomplete or deficient certificates to be corrected.
- j. Submit to FEMA, or require applicants to submit to FEMA, data and information necessary to maintain *FIRMs*, including *hydrologic and hydraulic engineering analyses* prepared by or for Calvert County, within six months after such data and information becomes available if the analyses indicate changes in base flood elevations.
- k. Maintain and permanently keep records that are necessary for the administration of these regulations, including:
 - i. *Flood Insurance Studies, Flood Insurance Rate Maps* (including historic studies and maps and current effective studies and maps) and Letters of Map Change; and
 - ii. Documentation supporting issuance and denial of permits, *Elevation Certificates*, documentation of the elevation (in relation to the datum on the *FIRM*) to which *structures* have been *floodproofed*, other required design certifications, *variances*, and records of enforcement actions taken to correct *violations* of these regulations.
- l. Enforce the provisions of these regulations, investigate *violations*, issue notices of *violations* or stop work orders, and require permit holders to take corrective action.

- m. Advise the Calvert County Board of Appeals regarding the intent of these regulations and, for each application for a *variance*, prepare a staff report and recommendation.
- n. Administer the requirements related to proposed work on existing buildings:
 - i. Make determinations as to whether buildings and *structures* that are located in *flood* hazard areas and that are damaged by any cause have been *substantially damaged*.
 - ii. Make reasonable efforts to notify owners of *substantially damaged structures* of the need to obtain a permit to repair, rehabilitate, or reconstruct, and prohibit the non-compliant repair of *substantially damaged* buildings except for temporary emergency protective measures necessary to secure a property or stabilize a building or *structure* to prevent additional damage.
- o. Undertake, as determined appropriate by the Floodplain Administrator due to the circumstances, other actions which may include but are not limited to: issuing press releases, public service announcements, and other public information materials related to permit requests and repair of damaged *structures*; coordinating with other Federal, State, and local agencies to assist with substantial damage determinations; providing owners of damaged *structures* information related to the proper repair of damaged *structures* in *special flood hazard areas*; and assisting property owners with documentation necessary to file claims for Increased Cost of Compliance coverage under NFIP flood insurance policies.
- p. Notify the Federal Emergency Management Agency when the corporate boundaries of Calvert County have been modified and:
 - i. Provide a map that clearly delineates the new corporate boundaries or the new area for which the authority to regulate pursuant to these regulations has either been assumed or relinquished through annexation; and
 - ii. If the *FIRM* for any annexed area includes *special flood hazard areas* that have *flood zones* that have regulatory requirements that are not set forth in these regulations,

prepare amendments to these regulations to adopt the *FIRM* and appropriate requirements, and submit the amendments to the governing body for adoption; such adoption shall take place within six months of the date of annexation and a copy of the amended regulations shall be provided to MDE (NFIP State Coordinator) and FEMA.

- q. Upon the request of FEMA, complete and submit a report concerning participation in the NFIP which may request information regarding the number of buildings in the SFHA, number of permits issued for *development* in the SFHA, and number of *variances* issued for *development* in the SFHA.

3. Use and Interpretation of FIRMs

The Floodplain Administrator shall make interpretations, where needed, as to the exact location of *special flood hazard areas*, *floodplain* boundaries, and *floodway* boundaries. The following shall apply to the use and interpretation of *FIRMs* and data:

- a. Where field surveyed topography indicates that ground elevations:
 - i. Are below the *base flood elevation*, even in areas not delineated as a *special flood hazard area* on a *FIRM*, the area shall be considered as *special flood hazard area* and subject to the requirements of these regulations;
 - ii. Are above the *base flood elevation*, the area shall be regulated as *special flood hazard area* unless the applicant obtains a *Letter of Map Change* that removes the area from the *special flood hazard area*.
- b. In FEMA-identified *special flood hazard areas* where *base flood elevation* and *floodway* data have not been identified and in areas where FEMA has not identified *special flood hazard areas*, any other flood hazard data available from a Federal, State, or other source shall be reviewed and reasonably used.
- c. *Base flood elevations* and designated *floodway* boundaries on *FIRMs* and in *FISs* shall take precedence over *base flood elevations* and *floodway* boundaries by any other sources if such sources show reduced *floodway* widths and/or lower *base*

flood elevations.

- d. Other sources of data shall be reasonably used if such sources show increased *base flood elevations* and/or larger *floodway* areas than are shown on *FIRMs* and in *FISs*.
 - e. If a Preliminary *Flood Insurance Rate Map* and/or a Preliminary *Flood Insurance Study* has been provided by FEMA:
 - i. Upon the issuance of a Letter of Final Determination by FEMA, the preliminary flood hazard data shall be used and shall replace the flood hazard data previously provided from FEMA for the purposes of administering these regulations.
 - ii. Prior to the issuance of a Letter of Final Determination by FEMA, the use of preliminary flood hazard data shall be deemed the best available data pursuant to Section 8-2.03.C.3 and used where no *base flood elevations* and/or *floodway* areas are provided on the effective *FIRM*.
 - iii. Prior to issuance of a Letter of Final Determination by FEMA, the use of preliminary flood hazard data is permitted where the preliminary *base flood elevations* or *floodway* areas exceed the *base flood elevations* and/or designated *floodway* widths in existing flood hazard data provided by FEMA. Such preliminary data may be subject to change and/or appeal to FEMA.
4. Permits Required and Expiration
- a. It shall be unlawful for any *person* to begin any *development* or construction which is wholly within, partially within, or in contact with any flood hazard area established in Section 8-2.03.C, including but not limited to: filling; grading; construction of new *structures*; the *substantial improvement* of buildings or *structures*, including repair of *substantial damage*; placement or replacement of *manufactured homes*, including *substantial improvement* or repair of *substantial damage* of *manufactured homes*; erecting or installing a *temporary structure*, or *alteration of a watercourse*, until a permit is obtained from Calvert County. No such permit shall be issued until the requirements of these regulations have been met.
 - b. In addition to the permits required in paragraph (A), applicants

for permits in *nontidal waters of the State* are advised to contact MDE. Unless waived by MDE, pursuant to Code of Maryland Regulations 26.17.04, Construction on Nontidal Waters and Floodplains, MDE regulates the “100-year frequency floodplain of free-flowing waters,” also referred to as *nontidal waters of the State*. To determine the 100-year frequency floodplain, hydrologic calculations are based on the ultimate *development* of the watershed, assuming existing zoning. The resulting flood hazard areas delineated using the results of such calculations may be different than the *special flood hazard areas* established in Section 8-2.03.C of these regulations.

- c. A permit in the 100-yr floodplain is valid provided the actual start of work is within 180 days of the date of permit issuance. Requests for extensions shall be submitted in writing. The Floodplain Administrator may grant, in writing, one or more extensions of time, for periods not more than 180 days each.

5. Application Required

- a. At a minimum, applications shall include:
 - i. Site plans drawn to scale showing the nature, location, dimensions, and existing and proposed topography of the area in question, and the location of existing and proposed *structures*, excavation, filling, storage of materials, drainage facilities, and other proposed activities.
 - ii. Elevation of the existing natural ground where buildings or *structures* are proposed, referenced to the datum on the *FIRM*.
 - iii. Delineation of flood hazard areas, designated *floodway boundaries*, *flood zones*, *base flood elevations*, and *flood protection setbacks*. *Base flood elevations* shall be used to delineate the boundary of flood hazard areas and such delineations shall prevail over the boundary of SFHAs shown on *FIRMs*.

- iv. Where floodways are not delineated or *base flood elevations* are not shown on the *FIRMs*, the Floodplain Administrator has the authority to require the applicant to use information provided by the Floodplain Administrator, information that is available from Federal, State, or other sources, or to determine such information using accepted engineering practices or methods approved by the Floodplain Administrator. [Note: See "Managing Floodplain Development in Approximate Zone A Areas: A Guide for Obtaining and Developing Base (100-Year) Flood Elevations" (FEMA 265).]
- v. Determination of the *base flood elevations*, for *development* proposals and subdivision proposals, each with at least 5 lots or at least 5 acres, whichever is the lesser, in *special flood hazard areas* where *base flood elevations* are not shown on the *FIRM*; if *hydrologic and hydraulic engineering analyses* are submitted, such analyses shall be performed in accordance with the requirements and specifications of MDE and FEMA.
- vi. *Hydrologic and hydraulic engineering analyses* for proposals in *special flood hazard areas* where FEMA has provided *base flood elevations* but has not delineated a *floodway*; such analyses shall demonstrate that the cumulative effect of proposed *development*, when combined with all other existing and anticipated development will not increase the water surface elevation of the *base flood* by more than one foot or a lower increase if required by MDE.
- vii. For encroachments in *floodways*, an evaluation of alternatives to such encroachments, including different uses of the site or portion of the site within the *floodway*, and minimization of such encroachment.
- viii. If fill is proposed to be placed for a purpose other than to elevate *structures*, the applicant shall indicate the intended purpose for the fill.
- ix. For proposed buildings and *structures*, including *substantial improvement* and repair of *substantial damage*, and placement and replacement of

manufactured homes, including *substantial improvement* and repair of *substantial damage*:

- (1) The proposed elevation of the *lowest floor*, including *basement*, referenced to the datum on the *FIRM* and a signed *Agreement to Submit an Elevation Certificate*.
 - (2) The signed *Declaration of Land Restriction (Nonconversion Agreement)* that shall be recorded on the property deed prior to issuance of the Certificate of Use and Occupancy, if the application includes an *enclosure below the lowest floor* or a crawl/underfloor space that is more than four (4) feet in height.
 - (3) A written evaluation of alternative methods considered to elevate *structures* and *manufactured homes*, if the location is in *nontidal waters of the State* and fill is proposed to achieve the elevation required in Section 8-2.03.J.4.a or J.5.a.
- x. For *accessory structures* that are 300 square feet or larger in area (footprint) that are below the *base flood elevation*, a *Declaration of Land Restriction (Nonconversion Agreement)* shall be recorded on the property deed prior to issuance of the Certificate of Use and Occupancy.
 - xi. For *temporary structures* and temporary storage, specification of the duration of the temporary use.
 - xii. For proposed work on existing buildings, *structure*, and *manufactured homes*, including any improvement, addition, repairs, alterations, rehabilitation, or reconstruction, sufficient information to determine if the work constitutes *substantial improvement* or repair of *substantial damage*, including but not limited to:
 - (1) If the existing building or *structure* was constructed after September 28, 1984, evidence that the work will not alter any aspect of the building or *structure* that was required for compliance with the floodplain management requirements in effect at the time the

building or *structure* was permitted.

- (2) If the proposed work is a horizontal addition, a description of the addition and whether it will be independently supported or structurally connected to the *base building* and the nature of all other modifications to the *base building*, if any.
 - (3) Documentation of the *market value* of the building or *structure* before the improvement or, if the work is repair of damage, before the damage occurred.
 - (4) Documentation of the actual cash value of all proposed work, including the actual cash value of all work necessary to repair and restore damage to the before-damaged condition, regardless of the amount of work that will be performed. The value of work performed by the owner or volunteers shall be valued at market labor rates; the value of donated or discounted materials shall be valued at market rates.
- xiii. Certifications and/or technical analyses prepared or conducted by a *licensed* professional engineer or *licensed* architect, as appropriate, including:
- (1) The determination of the *base flood elevations* or *hydrologic and hydraulic engineering analyses* prepared by a *licensed* professional engineer that are required by the Floodplain Administrator or are required by these regulations in: Section 8-2.03.I.2 for certain subdivisions and *development*; Section 8-2.03.J.3.a for *development* in designated *floodways*; Section 8-2.03.J.3.c for *development* in flood hazard areas with *base flood elevations* but no designated *floodways*; and Section 8-2.03.J.3.e for deliberate alteration or relocation of *watercourses*.
 - (2) The *Floodproofing Certificate* for nonresidential *structures* that are *floodproofed* as required in Section 8-2.03.J.5.b.
 - (3) Certification that engineered *flood openings* are designed to meet the minimum requirements of

Section 8-2.03.J.4.c.iii to automatically equalize hydrostatic flood forces.

- (4) Certification that the proposed elevation, structural design, specifications and plans, and the methods of construction to be used for *structures* in *coastal high hazard areas* (V Zones) and *Coastal A Zones*, are in accordance with accepted standards of practice and meet the requirements of Section 8-2.03.K.3.c.
- xiv. For nonresidential *structures* that are proposed with *floodproofing*, an operations and maintenance plan as specified in Section 8-2.03.J.5.b.iii.
- xv. Such other material and information as may be requested by the Floodplain Administrator and necessary to determine conformance with these regulations.

b. New Technical Data

- i. The applicant may seek a *Letter of Map Change* by submitting new technical data to FEMA, such as base maps, topography, and engineering analyses to support revision of *floodplain* and *floodway* boundaries and/or *base flood elevations*. Such submissions shall be prepared in a format acceptable to FEMA and any fees shall be the sole responsibility of the applicant. A copy of the submittal shall be attached to the application for a permit.
- ii. If the applicant submits new technical data to support any change in *floodplain* and designated *floodway* boundaries and/or *base flood elevations* but has not sought a *Letter of Map Change* from FEMA, the applicant shall submit such data to FEMA as soon as practicable, but not later than six months after the date such information becomes available. Such submissions shall be prepared in a format acceptable to FEMA and any fees shall be the sole responsibility of the applicant.

6. Review of Application

The Floodplain Administrator or designee shall:

- a. Review applications for *development* in *special flood hazard areas* to determine the completeness of information submitted. The applicant shall be notified of incompleteness or additional information that is required to support the application.
- b. Notify applicants that permits from MDE and the U.S. Army Corps of Engineers, and other State and Federal authorities may be required.
- c. Review all permit applications to assure that all necessary permits have been received from the Federal, State or local governmental agencies from which prior approval is required. The applicant shall be responsible for obtaining such permits, including permits issued by:
 - i. The U.S. Army Corps of Engineers under Section 10 of the Rivers and Harbors Act and Section 404 of the Clean Water Act;
 - ii. MDE pursuant to COMAR 26.23 (Nontidal Wetlands) and Section 401 of the Clean Water Act;
 - iii. MDE for construction on *nontidal waters of the State* pursuant to COMAR 26.17.04; and
 - iv. MDE pursuant to COMAR 26.24 (Tidal Wetlands).
- d. Review applications for compliance with these regulations after all information required in Section 8-2.03.H.1 of these regulations or identified and required by the Floodplain Administrator has been received.
- e. If the Floodplain Administrator or designee finds that the permit application is not in compliance with the Zoning Ordinance, he/she shall provide a referral to the Clerk of the Board of Appeals and to the applicant indicating the section of the Zoning Ordinance that prohibits the proposed activity. The Floodplain Administrator or designee shall also provide a staff report regarding the request prior to the Board of Appeals hearing.

7. Inspections

The Floodplain Administrator, or designee, shall make periodic inspections of *development* permitted in *special flood hazard areas*,

at appropriate times throughout the period of construction in order to monitor compliance. Such inspections may include:

- a. Stake-out inspection, to determine location on the site relative to the flood hazard area and designated *floodway*.
- b. Foundation inspection, upon placement of the *lowest floor* and prior to further vertical construction, to collect information or certification of the elevation of the *lowest floor*.
- c. Inspection of *enclosures below the lowest floor*, including crawl/underfloor spaces, to determine compliance with applicable provisions.
- d. Utility inspection, upon installation of specified equipment and appliances, to determine appropriate location with respect to the *base flood elevation*.
- e. Final inspection prior to issuance of the Certificate of Use and Occupancy.

8. Submissions Required Prior to Final Inspection

Pursuant to the *Agreement to Submit an Elevation Certificate* submitted with the application as required in Section 8-2.03.H.5.a.ix.(1), the permittee shall have an *Elevation Certificate* prepared and submitted prior to final inspection and issuance of a Certificate of Occupancy for elevated *structures* and *manufactured homes*, including new *structures* and *manufactured homes*, substantially-improved *structures* and *manufactured homes*, and additions to *structures* and *manufactured homes*. The Elevation Certificate shall be completed by a *licensed* professional land surveyor or a *licensed* professional engineer, as specified by the Floodplain Administrator. When used to document the height above grade of buildings in *special flood hazard areas* for which *base flood elevation* data are not available, the Elevation Certificate shall be completed in accordance with the instructions issued by FEMA.

[Note: FEMA Form 81-31 and instructions are available online at <http://www.fema.gov/library/viewRecord.do?id=1383>.]

I. Requirements In All Flood Hazard Areas

1. Application of Requirements

The general requirements of this section apply to all *development* proposed within all *special flood hazard areas* identified in Section 8-2.03.C.

2. Subdivision Proposals and Development Proposals

a. In all *flood zones*:

- i. Subdivision proposals and *development* proposals shall be consistent with the need to minimize flood damage and are subject to all applicable standards in these regulations.
- ii. Subdivision proposals and *development* proposals shall have utilities and facilities such as sewer, gas, electrical, and water systems located and constructed to minimize flood damage.
- iii. Subdivision proposals and *development* proposals shall have adequate drainage paths provided to reduce exposure to flood hazards and to guide floodwaters around and away from proposed *structures*.
- iv. Subdivision proposals and *development* proposals containing at least 5 lots or at least 5 acres, whichever is the lesser, that are wholly or partially in flood hazard areas where *base flood elevation* data are not provided by the Floodplain Administrator or available from other sources, shall be supported by determinations of *base flood elevations* as required in Section 8-2.03.H.5 of these regulations.
- v. Subdivision access roads shall have the driving surface at or above the *base flood elevation*.

b. In *special flood hazard areas* or *nontidal waters of the State*:

- i. Except for unavoidable road and driveway crossings and stormwater management, subdivision proposals shall be laid out such that proposed building pads and Building Restriction Lines are located outside of the *special flood hazard area* and any portion of platted lots that include land areas that are below the *base flood elevation* shall be used for other purposes, deed restricted, or otherwise protected to preserve it as open space. Natural vegetation shall be maintained or allowed to naturally regenerate in the special flood hazard area of a

subdivision. The control of invasive species during natural regeneration is encouraged.

- ii. Subdivision access roads shall have the driving surface at or above the *base flood elevation*.

3. Protection of Water Supply and Sanitary Sewage Systems

- a. New and replacement water supply systems shall be designed to minimize or eliminate infiltration of floodwaters into the systems.
- b. New and replacement sanitary sewage systems shall be designed to minimize or eliminate infiltration of floodwaters into systems and discharges from systems into floodwaters.
- c. On-site waste disposal systems shall be located to avoid impairment to or contamination from them during conditions of *flooding*.

4. Buildings and Structures

New buildings and *structures* (including the placement and replacement of *manufactured homes*) and *substantial improvement* of existing *structures* (including *manufactured homes*) that are located, in whole or in part, in any *special flood hazard area* shall:

- a. Be designed (or modified) and constructed to safely support flood loads. The construction shall provide a complete load path capable of transferring all loads from their point of origin through the load-resisting elements to the foundation. *Structures* shall be designed, connected and anchored to resist flotation, collapse or permanent lateral movement due to structural loads and stresses, including hydrodynamic and hydrostatic loads and the effects of buoyancy, from *flooding* equal to the *flood protection elevation* or the elevation required by these regulations or the *building code*, whichever is higher.
- b. Be constructed by methods and practices that minimize flood damage.
- c. Use *flood damage-resistant materials* below the elevation of the *lowest floor* required in Section 8-2.03.J.4.a (for A Zones) or Section 8-2.03.K.3.b (for V Zones and *Coastal A Zones*).

- d. Have electrical systems, equipment and components, and mechanical, heating, ventilating, air conditioning, and plumbing appliances, plumbing fixtures, duct systems, and other service equipment located at or above the elevation of the *lowest floor* required in Section 8-2.03.J.4.a or J.5.a (A Zones) or Section 8-2.03.K.3.b (V Zones and Coastal A Zones). Electrical wiring systems are permitted to be located below elevation of the *lowest floor* provided they conform to the provisions of the electrical part of the *building code* for wet locations. If replaced as part of a *substantial improvement*, electrical systems, equipment and components, and heating, ventilation, air conditioning, and plumbing appliances, plumbing fixtures, duct systems, and other service equipment shall meet the requirements of this section.
- e. As an alternative to paragraph (d), electrical systems, equipment and components, and heating, ventilating, air conditioning, and plumbing appliances, plumbing fixtures, duct systems, and other service equipment are permitted to be located below the elevation of the *lowest floor* provided they are designed and installed to prevent water from entering or accumulating within the components and to resist hydrostatic and hydrodynamic loads and stresses, including the effects of buoyancy, during the occurrence of flooding to that elevation.
- f. Have the electric panel-board elevated at least three (4) feet above the BFE.
- g. If located in flood hazard areas (A Zones) that are not identified as *Coastal A Zones* and *coastal high hazard areas* (V Zones), comply with the specific requirements of Section 8-2.03.J.
- h. If located in the *Coastal A Zone*, comply with the specific requirements of:
 - i. Section 8-2.03.K (new construction and placement of new manufactured homes); or
 - ii. Section 8-2.03.J (*substantial improvements* (including repair of *substantial damage*) and replacement of *manufactured homes*).

- i. If located in *coastal high hazard areas* (v Zones), comply with the specific requirements of Section 8-2.03.K.
- j. Comply with the requirements of the most restrictive designation if located on a site that has more than one *flood zone* designation (A Zone, designated *floodway*, *Coastal A Zone*, V Zone).

5. Placement of Fill

- a. Disposal of fill, including but not limited to earthen soils, rock, rubble, construction debris, woody debris, and trash, shall not be permitted in *special flood hazard areas*.
- b. Fill shall not be placed in *Coastal A Zones* or *coastal high hazard areas* (V Zones) except as provided in Section 8-2.03.K.2.
- c. Fill proposed to be placed to elevate *structures* in flood hazard areas (A Zones) that are not *Coastal A Zones* or *coastal high hazard areas* (V Zones) shall comply with the floodways requirements in Section 8-2.03.J.3.a, Section 5.3(B), and Section 5.3(C) and the limitations of Section 8-2.03.J.4.b.

6. Historic Features

Repair, alteration, addition, rehabilitation, or other improvement of *historic features* shall be subject to the requirements of these regulations if the proposed work is determined to be a *substantial improvement*, unless a determination is made that the proposed work will not preclude the *feature's* continued designation as a *historic feature*. The Floodplain Administrator may require documentation of a *structure's* continued eligibility and designation as a *historic feature*.

7. Manufactured Homes

- a. New *manufactured homes* shall not be placed or installed in *floodways* or *coastal high hazard areas* (V Zones).

- b. For the purpose of these regulations, the *lowest floor* of a *manufactured home* is the bottom of the lowest horizontal supporting member (longitudinal chassis frame beam).
- c. New *manufactured homes* located outside of *floodways* and *coastal high hazard areas* (V Zones), replacement *manufactured homes* in any flood hazard areas, and *substantial improvement* (including repair of *substantial damage*) of existing *manufactured homes* in all flood hazard area, shall:
 - i. Be elevated on a permanent, reinforced foundation in accordance with Section 8-2.03.J or K, as applicable to the *flood zone*;
 - ii. Be installed in accordance with the anchor and tie-down requirements of the *building code* or the manufacturer's written installation instructions and specifications; and
 - iii. Have *enclosures below the lowest floor* of the elevated *manufactured home*, if any, including enclosures that are surrounded by rigid skirting or other material that is attached to the frame or foundation, that comply with the requirements of Section 8-2.03.J or K, as applicable to the *flood zone*.

[Note: See "Protecting Manufactured Homes from Floods and Other Hazards: A Multi-Hazard Foundation and Installation Guide" (FEMA P-85).]

8. Recreational Vehicles

Recreational vehicles shall:

- a. Meet the requirements for *manufactured homes* in Section 8-2.03.I.7; or
- b. Be fully licensed and ready for highway use; or
- c. Be on a site for less than 180 consecutive days.

9. Critical and Essential Facilities

Critical and essential facilities shall:

- a. Not be located in *coastal high hazard areas* (V Zones).

- b. If located in flood hazard areas other than *coastal high hazard areas*, be elevated to the higher of elevation required by these regulations plus one (1) foot, the elevation required by the *building code*, or the elevation of the 0.2 percent chance (500-year) flood.

10. Temporary Structures and Temporary Storage

In addition to the application requirements of Section 8-2.03.H.5, applications for the placement or erection of *temporary structures* and the temporary storage of any goods, materials, and equipment, shall specify the duration of the temporary use. *Temporary structures* and temporary storage in *floodways* shall meet the limitations of Section 8-2.03.J.3.a of these regulations. In addition:

a. *Temporary structures* shall:

- i. Be designed and constructed to prevent flotation, collapse or lateral movement resulting from hydrodynamic loads and hydrostatic loads during conditions of the *base flood*;
- ii. Have electric service installed in compliance with the electric code; and
- iii. Comply with all other requirements of the applicable State and local permit authorities.

b. Temporary storage shall not include hazardous materials.

11. Gas or Liquid Storage Tanks

- a. Underground tanks in flood hazard areas shall be anchored to prevent flotation, collapse or lateral movement resulting from hydrostatic loads, including the effects of buoyancy, during conditions of the *base flood*.
- b. Above-ground tanks in flood hazard areas shall be anchored to a supporting structure and elevated to or above the *base flood elevation*, or shall be anchored or otherwise designed and constructed to prevent flotation, collapse, or lateral movement resulting from hydrodynamic and hydrostatic loads, including the effects of buoyancy, during conditions of the *base flood*.

- c. In flood hazard areas, tank inlets, fill openings, outlets and vents shall be:
 - i. At or above the *base flood elevation* or fitted with covers designed to prevent the inflow of floodwater or outflow of the contents of the tanks during conditions of the *base flood*; and
 - ii. Anchored to prevent lateral movement resulting from hydrodynamic and hydrostatic loads, including the effects of buoyancy, during conditions of the *base flood*.

12. Functionally Dependent Uses

Applications for *functionally dependent uses* that do not conform to the requirements of these regulations shall be approved only by *variances* issued pursuant to Section 8-2.03.L. If approved, *functionally dependent uses* shall be protected by methods that minimize flood damage during the *base flood*, including measures to allow floodwaters to enter and exit, use of *flood damage-resistant materials*, and elevation of electric service and equipment to the extent practical given the use of the building.

J. Requirements In Flood Hazard Areas (A Zones) That Are Not Coastal High Hazard Areas Or Coastal A Zones

1. General Requirements

In addition to the general requirements of Section 8-2.03.I, the requirements of this section shall:

- a. Apply in flood hazard areas that are not identified as *coastal high hazard areas (V Zones)* or *Coastal A Zones*. These flood hazard areas, referred to collectively as "A Zones," include *special flood hazard areas along nontidal waters of the State* landward *coastal high hazard areas (V Zones)*, and landward of *Coastal A Zones* (if delineated).
- b. Apply to all development, new construction, substantial improvements (including repair of substantial damage), and placement, replacement, and substantial improvement (including repair of substantial damage) of manufactured homes.

c. Development in Areas with Base Flood Elevations but No Designated Floodways

For development in special flood hazard areas of nontidal waters of the State with base flood elevations but no designated floodways:

- i. The applicant shall develop *hydrologic and hydraulic engineering analyses* and technical data reflecting the proposed activity and shall submit such technical data to the Floodplain Administrator as required in Section 8-2.03.H.4.a. The analyses shall be prepared by a *licensed* professional engineer in a format required by FEMA for a Conditional Letter of Map Revision or Letter of Map Revision. Submittal requirements and fees shall be the responsibility of the applicant.
- ii. The proposed *development* may be permitted if the applicant has received a permit by MDE and if the analyses demonstrate that the cumulative effect of the proposed *development*, when combined with all other existing and potential flood hazard area encroachments will not increase the *base flood elevation* more than 1.0 foot at any point.

d. Construction of Roads, Bridges, Culverts, Dams and In-Stream Ponds

Construction of roads, bridges, culverts, dams, and in-stream ponds in *nontidal waters of the State* shall not be approved unless they comply with this section and the applicant has received a permit from MDE.

e. Alteration of a Watercourse

For any proposed *development* that involves *alteration of a watercourse* not subject to paragraph (c), unless waived by MDE, the applicant shall develop *hydrologic and hydraulic engineering analyses* and technical data reflecting such changes, including the *floodway* analysis required in Section 8-2.03.H.4.a, and submit such technical data to the Floodplain Administrator and to FEMA. The analyses shall be prepared by a *licensed* professional engineer in a format required by MDE and by FEMA for a Conditional Letter of Map Revision or Letter

of Map Revision. Submittal requirements and fees shall be the responsibility of the applicant.

Alteration of a watercourse may be permitted only upon submission, by the applicant, of the following:

- i. A description of the extent to which the *watercourse* will be altered or relocated;
- ii. A certification by a *licensed* professional engineer that the flood-carrying capacity of the *watercourse* will not be diminished;
- iii. Evidence that adjacent communities, the U.S. Army Corps of Engineers, and MDE have been notified of the proposal, and evidence that such notifications have been submitted to FEMA; and
- iv. Evidence that the applicant shall be responsible for providing the necessary maintenance for the altered or relocated portion of the *watercourse* so that the flood carrying capacity will not be diminished. The Floodplain Administrator may require the applicant to enter into an agreement with Calvert County specifying the maintenance responsibilities; if an agreement is required, the permit shall be conditioned to require that the agreement be recorded on the deed of the property which shall be binding on future owners.

3. Residential Structures and Residential Portions of Mixed Use Structures

New residential *structures* and residential portions of mixed use *structures*, and *substantial improvement* (including repair of *substantial damage*) of existing residential *structures* and residential portions of mixed use *structures* shall comply with the applicable requirements of Section 8-2.03.I and this section. See Section 8-2.03.J.6 for requirements for horizontal additions.

a. Elevation Requirements

- i. *Lowest floors* shall be elevated to or above the *flood protection elevation*.

- ii. In *areas of shallow flooding* (Zone AO), the *lowest floor* (including *basement*) shall be elevated at least as high above the *highest adjacent grade* as the depth number specified in feet on the *FIRM* plus two (2) feet, or at least four (4) feet if a depth number is not specified. *Enclosures below the lowest floor* shall meet the requirements of paragraph (c).

b. Limitations on Use of Fill to Elevate Structures

Unless otherwise restricted by these regulations, especially by the limitations in Section 8-2.03.J.3.a, b, and c, fill placed for the purpose of raising the ground level to support a building or *structure* shall:

- i. Consist of earthen soil or rock materials only.
- ii. Extend laterally from the building footprint to provide for adequate access as a function of use; the Floodplain Administrator may seek advice from the State Fire Marshal's Office and/or the local fire services agency;
- iii. Comply with the requirements of the *building code* and be placed and compacted to provide for stability under conditions of rising and falling floodwaters and resistance to erosion, scour, and settling;
- iv. Be sloped no steeper than one (1) vertical to two (2) horizontal, unless approved by the Floodplain Administrator;
- v. Be protected from erosion associated with expected velocities during the occurrence of the *base flood*; unless approved by the Floodplain Administrator, fill slopes shall be protected by vegetation if the expected velocity is less than five feet per second, and by other means if the expected velocity is five feet per second or more; and
- vi. Be designed with provisions for adequate drainage and no adverse effect on adjacent properties.

c. Enclosures Below the Lowest Floor

- i. *Enclosures below the lowest floor* shall be used solely for parking of vehicles, building access, crawl/underfloor

spaces, or limited storage.

- ii. *Enclosures below the lowest floor* shall be constructed using *flood damage-resistant materials*.
- iii. *Enclosures below the lowest floor* shall be provided with *flood openings* which shall meet the following criteria:
 [Note: See NFIP Technical Bulletin #1, "Openings in Foundation Walls and Walls of Enclosures Below Elevated Buildings."]
 (1) There shall be a minimum of two *flood openings* on different sides of each enclosed area; if a building has more than one *enclosure below the lowest floor*, each such enclosure shall have *flood openings* on exterior walls.
 (2) The total net area of all *flood openings* shall be at least 1 square inch for each square foot of enclosed area (non-engineered *flood openings*), or the *flood openings* shall be engineered *flood openings* that are designed and certified by a *licensed* professional engineer to automatically allow entry and exit of floodwaters; the certification requirement may be satisfied by an individual certification or an Evaluation Report issued by the ICC Evaluation Service, Inc.
 (3) The bottom of each *flood opening* shall be 1 foot or less above the higher of the interior floor or grade, or the exterior grade, immediately below the opening.
 (4) Any louvers, screens or other covers for the *flood openings* shall allow the automatic flow of floodwaters into and out of the enclosed area.
 (5) If installed in doors, *flood openings* that meet requirements of paragraphs (1) through (4), are acceptable; however, doors without installed *flood openings* do not meet the requirements of this section.

4. Nonresidential Structures and Nonresidential Portions of Mixed Use Structures

New nonresidential *structures* and nonresidential portions of mixed use *structures*, and *substantial improvement* (including repair of *substantial damage*) of existing nonresidential *structures* and nonresidential portions of mixed use *structures* shall comply with the applicable requirements of Section 8-2.03.I and the requirements of this section. See Section 8-2.03.J.6 for requirements for horizontal additions.

a. Elevation Requirements

Elevated *structures* shall:

- i. Have the *lowest floor* (including *basement*) elevated to or above the *flood protection elevation*; or
- ii. In *areas of shallow flooding* (Zone AO), have the *lowest floor* (including *basement*) elevated at least as high above the *highest adjacent grade* as the depth number specified in feet on the *FIRM* plus two (2) feet, or at least four (4) feet if a depth number is not specified; and
- iii. Have *enclosures below the lowest floor*, if any, that comply with the requirements of Section 8-2.03.J.4.c; or
- iv. If proposed to be elevated on fill, meet the limitations on fill in Section 8-2.03.J.4.b.

b. Floodproofing Requirements

- i. *Floodproofing* of new nonresidential buildings:
 - (1) Is not allowed in *nontidal waters of the State* (COMAR 26.17.04.11(B)(7)).
 - (2) Is not allowed in *Coastal A Zones*.
- ii. *Floodproofing* for *substantial improvement* of nonresidential buildings:
 - (1) Is allowed in *nontidal waters of the State*.
 - (2) Is allowed in *Coastal A Zones*.

- iii. If *floodproofing* is proposed, *structures* shall:
- (1) Be designed to be dry *floodproofed* such that the building or *structure* is watertight with walls and floors substantially impermeable to the passage of water to the level of the *flood protection elevation* plus 1.0 foot, or
 - (2) If located in an *area of shallow flooding* (Zone AO), be dry *floodproofed* at least as high above the *highest adjacent grade* as the depth number specified on the *FIRM* plus three (3) feet, or at least five (5) feet if a depth number is not specified; and
 - (3) Have structural components capable of resisting hydrostatic and hydrodynamic loads and effects of buoyancy;
 - (4) Have *floodproofing* measures that are designed taking into consideration the nature of flood-related hazards; frequency, depth and duration of *flooding*; rate of rise and fall of floodwater; soil characteristics; flood-borne debris; at least 12 hours of flood warning time from a credible source; and time necessary to implement any measures that require human intervention;
 - (5) Have at least one door above the applicable flood elevation that allows human ingress and egress during conditions of *flooding*;
 - (6) Have an operations and maintenance plan that is filed with local emergency management officials and that specifies the owner/occupant's responsibilities to monitor flood potential; the location of any shields, doors, closures, tools, or other goods that are required for implementation; maintenance of such goods; methods of installation; and periodic inspection; and

- (7) Be certified by a *licensed* professional engineer or *licensed* architect, through execution of a *Floodproofing Certificate* that states that the design and methods of construction meet the requirements of this section. The *Floodproofing Certificate* shall be submitted with the construction drawings as required in Section 8-2.03.H.5.a.xiii.

5. Horizontal Additions

- a. A horizontal addition proposed for a building or *structure* that was constructed after the date specified in Section 8-2.03.A.2 shall comply with the applicable requirements of Section 8-2.03.I and this section.
- b. In *nontidal waters of the State* that are subject to the regulatory authority of MDE, all horizontal additions shall comply with the applicable requirements of Section 8-2.03.I and this section and:
- i. If the addition is structurally connected to the *base building*, the requirements of paragraph (c) apply.
- ii. If the addition has an independent foundation and is not structurally connected to the *base building* and the common wall with the *base building* is modified by no more than a doorway, the *base building* is not required to be brought into compliance.
- c. For horizontal additions that are structurally connected to the *base building*:
- i. If the addition combined with other proposed repairs, alterations, or modifications of the *base building* constitutes *substantial improvement*, the *base building* and the addition shall comply with the applicable requirements of Section 8-2.03.I and this section.
- ii. If the addition constitutes *substantial improvement*, the *base building* and the addition shall comply with all of the applicable requirements of Section 8-2.03.I and this section.

- d. For horizontal additions with independent foundations that are not structurally connected to the *base building* and the common wall with the *base building* is modified by no more than a doorway, the *base building* is not required to be brought into compliance.

6. Accessory Structures

- a. In the 100-yr floodplain, detached *accessory structures* shall be limited to no more than 300 square feet in floor area and shall be used solely for parking of vehicles and limited storage.
- b. In the 100-yr floodplain, garages attached to the primary structure shall be elevated to the greatest extent possible, but may be permitted as an exemption to the strict elevation requirement if it is no more than 600 square feet in area and meets the requirement of 8-2.03.J.6.c.
- c. *Accessory structures* shall comply with the elevation requirements and other requirements of Section 8-2.03.J.4, the *floodproofing* requirements of Section 8-2.03.J.5.b, or shall:
 - i. Be useable only for parking of vehicles or limited storage;
 - ii. Be constructed with *flood damage-resistant materials* below the *base flood elevation*;
 - iii. Be constructed and placed to offer the minimum resistance to the flow of floodwaters;
 - iv. Be anchored to prevent flotation;
 - v. Have electrical service and mechanical equipment elevated to or above the *base flood elevation*; and
 - vi. Have *flood openings* that meet the requirements of Section 8-2.03.J.4.c.

K. Requirements in Coastal High Hazard Areas (V Zones) and Coastal A Zones

1. General Requirements

In addition to the general requirements of Section 8-2.03.I, the requirements of this section shall:

- a. Apply in flood hazard areas that are identified as *coastal high hazard areas* (V Zones) and *Coastal A Zones* (if delineated).
- b. Apply to all development, *new construction, substantial improvements* (including repair of *substantial damage*), and placement, replacement, and *substantial improvement* (including repair of *substantial damage*) of *manufactured homes*.

Exception: In *Coastal A Zones*, the requirements of Section 5.0 shall apply to *substantial improvements* (including repair of *substantial damage*), and *substantial improvement* of manufactured homes (including repair of *substantial damage*) and replacement *manufactured homes*.

[Note: See Coastal Construction Manual (FEMA 55).]

2. Location and Site Preparation

- a. The placement of structural fill for the purpose of elevating buildings is prohibited.
- b. Buildings shall be located landward of the reach of mean high tide.
- c. Minor grading, and the placement of minor quantities of fill, shall be permitted for landscaping and for drainage purposes under and around buildings and for support of parking slabs, pool decks, patios and walkways.
- d. Site preparations shall not alter sand dunes unless an engineering analysis demonstrates that the potential for flood damage is not increased.

c. Certification of Design

As required in Section 8-2.03.H.5.a.xiii, the applicant shall include in the application a certification prepared by a *licensed* professional engineer or a *licensed* architect that the design and methods of construction to be used meet the requirements of paragraph (a), paragraph (b), paragraph (d), and the *building code*.

d. Enclosures Below the Lowest Floor

- i. *Enclosures below the lowest floor* shall be used solely for parking of vehicles, building access or limited storage.
- ii. *Enclosures below the lowest floor* shall be less than 299 square feet in area (exterior measurement).
- iii. Walls and partitions are permitted below the elevated floor, provided that such walls and partitions are designed to break away under flood loads and are not part of the structural support of the building or *structure*. [Note: See NFIP Technical Bulletin #9, "Design and Construction Guidance for Breakaway Walls."]
- iv. Electrical, mechanical, and plumbing system components shall not be mounted on or penetrate through walls that are designed to break away under flood loads.
- v. Walls intended to break away under flood loads shall be constructed with insect screening or open lattice, or shall be designed to break away or collapse without causing collapse, displacement or other structural damage to the elevated portion of the building or supporting foundation system. Such walls, framing and connections shall have a design safe loading resistance of not less than 10 pounds per square foot and no more than 20 pounds per square foot; or
- vi. Where wind loading values of the *building code* exceed 20 pounds per square foot, the applicant shall submit a certification prepared and sealed by a *licensed* professional engineer or *licensed* architect that:
 - (1) The walls and partitions below the *lowest floor* have been designed to collapse from a water load less

than that which would occur during the *base flood*.

- (2) The elevated portion of the building and supporting foundation system have been designed to withstand the effects of wind and flood loads acting simultaneously on all building components (structural and nonstructural). Water loading values used shall be those associated with the *base flood*; wind loading values used shall be those required by the *building code*.
- (3) In *Coastal A Zones*, in addition to the requirements of this section, walls below the *lowest floor* shall have *flood openings* that meet the requirements of Section 8-2.03.J. 4.c.iii.

4. Horizontal Additions to Structures

- a. A horizontal addition proposed for a building or *structure* that was constructed after the date specified in Section 8-2.03.A.2 shall comply with the applicable requirements of Section 8-2.03.I and this section.
- b. For horizontal additions, whether structurally connected or not structurally connected, to the *base building*:
 - i. If the addition combined with other proposed repairs, alterations, or modifications of the *base building* constitutes *substantial improvement*, the *base building* and the addition shall comply with the applicable requirements of Section 8-2.03.I and this section.
 - ii. If the addition constitutes *substantial improvement*, the *base building* and the addition shall comply with all of the applicable requirements of Section 8-2.03.I and this section. [Note: The *base building* is required to comply otherwise it is an obstruction that does not comply with the *free-of-obstruction* requirement that applies to the elevated addition, see Section 8-2.03.K.3.b.iii.]

5. Accessory Structures

- a. *Accessory structures* shall be limited to no more than 300 square feet in floor area.
- b. *Accessory structures* shall comply with the elevation requirements and other requirements of Section 8-2.03.K.3 or, if not elevated, shall:
 - i. Be useable only for parking of vehicles or limited storage;
 - ii. Be constructed with *flood damage-resistant materials* below the *base flood elevation*;
 - iii. Be constructed and placed to offer the minimum resistance to the flow of floodwaters;
 - iv. Be anchored to prevent flotation;
 - v. Have electrical service and mechanical equipment elevated to or above the *base flood elevation*; and
 - vi. If larger than 100 square feet in size, have walls that meet the requirements of Section 8-2.03.K.3.d.iii through vi, as applicable for the *flood zone*; and if located in *Coastal A Zones*, walls shall have *flood openings* that meet the requirements of Section 8-2.03.J.4.c.iii.

6. Other Structures and Development

[Note: See NFIP Technical Bulletin #5, "Free-of-Obstruction Requirements."]

a. Decks and Patios

In addition to the requirements of the *building code* or the residential code, decks and patios shall be located, designed, and constructed in compliance with the following:

- i. A deck that is structurally attached to a building or *structure* shall have the bottom of the lowest horizontal structural member at or above the *flood protection elevation* and any supporting members that extend below the design flood elevation shall comply with the foundation

requirements that apply to the building or *structure*, which shall be designed to accommodate any increased loads resulting from the attached deck.

- ii. A deck or patio that is located below the *flood protection elevation* shall be structurally independent from *structures* and their foundation systems, and shall be designed and constructed either to remain intact and in place during *base flood* conditions or to break apart into small pieces that will not cause structural damage to adjacent elevated *structures*.
- iii. A deck or patio that has a vertical thickness of more than 12 inches or that is constructed with more than the minimum amount of fill that is necessary for site drainage shall not be approved unless an analysis demonstrates no harmful diversion of floodwaters or wave run-up and wave reflection that would increase damage to adjacent elevated *structures*.
- iv. A deck or patio that has a vertical thickness of 12 inches or less and that is at natural grade or on fill material that is similar to and compatible with local soils and is the minimum amount necessary for site drainage may be approved without requiring analysis of the impact on diversion of floodwaters or wave run-up and wave reflection.

b. Other Development

Other *development* activities shall be permitted only if located outside the footprint of, and not structurally attached to, *structures*, and only if an analysis demonstrates no harmful diversion of floodwaters or wave run-up and wave reflection onto adjacent elevated *structures*. Other *development* includes but is not limited to:

- i. Bulkheads, seawalls, retaining walls, revetments, and similar erosion control structures;
- ii. Solid fences, privacy walls, and fences prone to trapping debris, unless designed and constructed to fail under *base flood* conditions; and

iii. Mounded septic systems.

L. Variances

The Board of Appeals shall have the power to consider and authorize or deny *variances* from the strict application of the requirements of these regulations. A *variance* shall be approved only if it is determined to not be contrary to the public interest and where, owing to special conditions of the lot or parcel, a literal enforcement of the provisions of these regulations, an unnecessary hardship would result. Administrative variances are not allowed for variances to floodplain criteria. See Section 11-1.01.D.

M Enforcement

1. No building, *structure* or *development* shall hereafter be located, erected, constructed, reconstructed, improved, repaired, extended, converted, enlarged or altered without full compliance with the floodplain regulations (Section 8-2.03) and all other applicable regulations.
2. Failure to obtain a permit for development in the floodplain shall be a *violation* of these regulations and shall be subject to penalties in accordance with Section 8-2.08 and Section 1-7 of the Zoning Ordinance.
3. Permits issued on the basis of plans and applications approved by the Floodplain Administrator authorize only the specific activities set forth in such approved plans and applications or amendments thereto. Use, arrangement, or construction of such specific activities in the floodplain that are contrary to that authorization shall be deemed a *violation* of these regulations.

Section 8-2.08

8-2.08 Fines, Penalties and Mitigation

- A. In addition to the fines and penalties provided for in Section 1-7 of this Zoning Ordinance, the following shall apply to violations of Section 8-2:
 1. Any person in violation of Section 8-2.04 (Slopes 25 Percent or Greater and Erodible Soils Adjoining Streams) shall pay a fine not to exceed \$1,000 for each violation and shall be required to replant

trees to replace those that have been removed as prescribed in paragraph 'B' of this Section.

2. Any person in violation of Section 8-2.05 (Wetlands) or 8-2.06 (Development Adjacent to Perennial and Intermittent Streams) shall pay a fine not to exceed \$1,000 for each violation and shall be required to mitigate as prescribed in paragraph 'B' of this Section for the area impacted, filled, cleared, graded, or cut in violation of these sections.

3. Violations to the Floodplain Regulations

If the Floodplain Administrator determines that there has been a *violation* of any provision of the floodplain regulations (Section 8-2.03), the Floodplain Administrator shall give notice of such *violation* to the property owner, the owner's authorized agent, and the *person* responsible for such *violation*, and may issue a stop work order. The notice of *violation* or stop work order shall be in writing and shall:

- a. Include a list of *violations*, referring to the section or sections of these regulations that have been violated;
- b. Order remedial action which, if taken, will effect compliance with the provisions of these regulations;
- c. Specify a reasonable period of time to correct the *violation*;
- d. Advise the recipients of the right to appeal; and
- e. Be served in person; or
- f. Be posted in a conspicuous place in or on the property and sent by registered or certified mail to the last known mailing address, residence, or place of business of the recipients.
- g. Be subject to the penalties described in 8-2.08.D

- B. Replanting to correct a violation shall be calculated at the rate of four square feet to one square foot (4:1) of the area cleared, graded, cut, impacted or filled in violation of the provisions of this Section. A mitigation plan shall be approved by the Department of Planning and Zoning and shall include canopy trees at a rate equal to one large tree per 400 square feet, and in the same 400 sq. ft. either two understory trees or three shrubs selected from the document entitled, "Calvert County Native Plant List", adopted by the Board of County Commissioners and available from the Department of Planning and Zoning. In cases where there is less area than needed to replant at 4:1, the remainder shall be mitigated with the payment of fees-in-lieu as set by the Board of County Commissioners.

- C. A person required to conduct replanting as part of a mitigation plan shall post a bond or other financial security to insure compliance with the mitigation plan.
1. Requirements
 - a. A financial security shall be furnished in the form of a surety bond, an irrevocable letter of credit, cash bond, certificate of guarantee, or other surety as authorized from time to time by the Board of County Commissioners and approved by the Office of the County Attorney. The surety shall:
 - i. Name the Board of County Commissioners as obligee;
 - ii. Assure that the mitigation replanting is conducted in accordance with the approved mitigation plan;
 - iii. Be in an amount equal to 1.0 times the cost as approved by the Department of Planning and Zoning of performing the mitigation plus an administrative fee as set by the County Commissioners to cover the costs of inspections and handling of the bond. This fee will be submitted with the bond and will not be reimbursed, but placed in the Planning and zoning Environmental Review Fund;
 - iv. Remain in force until all requirements of the mitigation plan have been fulfilled to the satisfaction of the Department of Planning and Zoning.
 - b. The surety may not be cancelled by the issuing entity unless both of the following requirements are fulfilled:
 - i. The issuer notifies the Board of County Commissioners and the principal of its intention to cancel the surety, in writing, by registered mail, not less than 90 days before cancellation; and
 - ii. At least 45 days before the cancellation date indicated in the notice, the principal files a commitment from another entity to provide a substitute surety that will be effective on the cancellation date indicated in the notice.
 2. Forfeiture of Surety
 - a. The surety shall be subject to forfeiture if the principal fails to comply with the mitigation plan.
 - b. Before forfeiture of the surety, the Board of County Commissioners shall notify the principal and the issuer, by certified mail, of the failure of the principal to comply with the mitigation plan and shall give the principal 30 days to come into compliance.

- c. If a person fails to come into compliance within the 30-day period, the surety shall be forfeited and the County or its agents shall be allowed access to the property to accomplish the previously bonded planting.
- 3. Release of Surety.
 - a. If, after two growing seasons, the survival of plantings associated with the mitigation plan meets or exceeds the standards of the mitigation plan, the amount of the surety shall be released.
 - b. If, after two growing seasons, the survival of the plantings associated with the mitigation plan is less than the standards of the mitigation plan, the surety shall be reduced by a percentage equal to the percentage of plantings that have survived and that portion of the surety shall be released. An additional administrative fee as set by the County Commissioners will be submitted prior to partial release of the surety to cover the costs of additional inspections and handling of the remaining bond. This fee will not be reimbursed, but placed in the Planning and Zoning Environmental Review Fund.
- D. *Violations* of the floodplain regulations (Section 8-2.03) or failure to comply with the requirements of these regulations or any conditions attached to a permit or *variance* shall constitute a misdemeanor. Any *person* responsible for a *violation* shall comply with the notice of *violation* or stop work order. Failure to comply shall require a fine of \$500 plus compliance must be achieved. Each day a *violation* continues shall be considered a separate offense. Nothing herein contained shall prevent Calvert County from taking such other lawful action as is necessary to prevent or remedy any *violation*.

Section 11-1.01.D

- D. Variances; Floodplain.
 - 1. a. The Board of Appeals shall have the power to consider and authorize or deny *variances* from the strict application of the requirements of Section 8-2.03. Administrative variances are not allowed for variances to floodplain criteria.
 - b. Upon consideration of the purposes of these regulations, the individual circumstances, and the considerations and limitations of this section, the Board of Appeals may attach such conditions to

3. Considerations for Variances

The Board of Appeals Administrator shall request comments on *variance* applications from MDE (NFIP State Coordinator) and County Floodplain Administrator and shall provide such comments to the Board of Appeals. In considering *variance* applications, the Board of Appeals shall consider and make findings of fact on all evaluations, all relevant factors, requirements specified in other sections of the Zoning Ordinance including Section 11-1.01.A and the following factors:

- a. The danger that materials may be swept onto other lands to the injury of others..
- b. The danger to life and property due to *flooding* or erosion damage.
- c. The susceptibility of the proposed *development* and its contents (if applicable) to flood damage and the effect of such damage on the individual owner.
- d. The availability of alternative locations for the proposed use which are not subject to, or are subject to less, *flooding* or erosion damage.
- e. The necessity to the facility of a waterfront location, where applicable, or if the facility is a *functionally dependent use*.
- f. The compatibility of the proposed use with existing and anticipated *development*.
- g. The relationship of the proposed use to the comprehensive plan for that area.
- h. The safety of access to the property in times of flood for passenger vehicles and emergency vehicles.
- i. The expected heights, velocity, duration, rate of rise, and sediment transport of the floodwaters and the effects of wave action, if applicable, expected at the site.
- j. The costs of providing government services during and after flood conditions, including maintenance and repair of public utilities and facilities such as sewer, gas, electrical, and water systems, and streets and bridges.
- k. The comments provided by MDE (NFIP State Coordinator).

4. Limitations for Granting Variances

The Board of Appeals shall make an affirmative decision on a *variance* request only upon:

- a. A showing of good and sufficient cause.
- b. A determination that failure to grant the *variance* would result in exceptional hardship due to the physical characteristics of the property. Increased cost or inconvenience of meeting the requirements of these regulations does not constitute an exceptional hardship to the applicant.
- c. A determination that the granting of a *variance* for *development* within any designated *floodway*, or flood hazard area with *base flood elevations* but no designated *floodway*, will not result in increased flood heights beyond that which is allowed in these regulations.
- d. A determination that the granting of a *variance* will not result in additional threats to public safety; extraordinary public expense, nuisances, fraud or victimization of the public, or conflict with existing local laws.
- e. A determination that the building, *structure* or other *development* is protected by methods to minimize flood damages.
- f. A determination that the *variance* is the minimum necessary to afford relief, considering the flood hazard.
- g. The approval of the *variance* is not contrary to the public interest.

Article 12 Definitions

<u>Term</u>	<u>Definition</u>
Accessory Building, Structure, or Use	A building, structure, or use on the same lot with, detached from, and of a nature customarily incidental and subordinate to, a principal building, structure, or use. In the 100-yr floodplain, an accessory structure shall be used solely for parking of vehicles and limited storage.
Agreement to Submit an Elevation Certificate	<p>A form on which the applicant for a permit to construct a building or <i>structure</i>, to construct certain horizontal additions, to place or replace a <i>manufactured home</i>, to substantially improve a building, <i>structure</i>, or <i>manufactured home</i>, agrees to have an <i>Elevation Certificate</i> prepared by a <i>licensed</i> professional engineer or <i>licensed</i> professional surveyor, as specified by the Floodplain Administrator, and to submit the certificate:</p> <ul style="list-style-type: none"> (1) Upon placement of the <i>lowest floor</i> and prior to further vertical construction; and (2) Prior to the final inspection and issuance of the Certificate of Occupancy.
Alteration of a Watercourse	For the purpose of the floodplain regulations, alteration of a watercourse includes, but is not limited to widening, deepening or relocating the channel, including excavation or filling of the channel. Alteration of a watercourse does not include construction of a road, bridge, culvert, dam, or in-stream pond unless the channel is proposed to be realigned or relocated as part of such construction.
Area of Shallow Flooding	A designated Zone AO on the <i>Flood Insurance Rate Map</i> with a 1-percent annual chance or greater of <i>flooding</i> to an average depth of one to three feet where a clearly defined channel does not exist, where the path of <i>flooding</i> is unpredictable, and where velocity flow may be evident; such <i>flooding</i> is characterized by ponding or sheet flow.
Base Building	The building to which an addition is being added. This term is used in provisions relating to additions in the 100-yr floodplain.
Base Flood	The <i>flood</i> having a one-percent chance of being equaled or exceeded in any given year; the base flood also is referred to as the 1-percent annual chance (100-year) <i>flood</i> .

<u>Term</u>	<u>Definition</u>
Base Flood Elevation	The water surface elevation of the <i>base flood</i> in relation to the datum specified on the <i>community's Flood Insurance Rate Map</i> . In <i>areas of shallow flooding</i> , the base flood elevation is the highest adjacent natural grade elevation plus the depth number specified in feet on the <i>Flood Insurance Rate Map</i> , or at least four (4) feet if the depth number is not specified.
Basement	Any area of the building having its floor subgrade (below ground level) on all sides.
Building Code(s)	The effective Maryland Building Performance Standards (COMAR 05.12.07), including the building code, residential code, and existing building code.
Coastal A Zone	An area within a <i>special flood hazard area</i> , landward of a coastal high hazard area (V Zone) or landward of a shoreline without a mapped coastal high hazard area, in which the principal source(s) of <i>flooding</i> are astronomical tides and storm surges, and in which, during <i>base flood</i> conditions, the potential exists for breaking waves with heights greater than or equal to 1.5 feet. The inland limit of the Coastal A Zone may be delineated on <i>FIRMs</i> as the "Limit of Moderate Wave Action."
Coastal High Hazard Area	An area of special flood hazard extending from offshore to the inland limit of a primary frontal dune along an open coast and any other area subject to high velocity wave action from storms. <i>Coastal high hazard areas</i> also are referred to as "V Zones" and are designated on <i>FIRMs</i> as zones VE or V1-30.
Community, Relative to Floodplain Management	A political subdivision of the State of Maryland (county, city or town) that has authority to adopt and enforce floodplain management regulations within its jurisdictional boundaries.
Critical and Essential Facilities	Buildings and other <i>structures</i> that are intended to remain operational in the event of extreme environmental loading from flood, wind, snow or earthquakes. [Note: See Maryland Building Performance Standards, Sec. 1602 and Table 1604.5.] Critical and essential facilities typically include hospitals, fire stations, police stations, storage of critical records, facilities that handle or store hazardous materials, and similar facilities.

<u>Term</u>	<u>Definition</u>
Declaration of Land Restriction (Nonconversion Agreement)	A form signed by the owner to agree not to convert or modify in any manner that is inconsistent with the terms of the permit and these regulations, certain <i>enclosures below the lowest floor</i> of elevated buildings and certain <i>accessory structures</i> . The form requires the owner to record it on the property deed to inform future owners of the restrictions.
Development	Any activity, other than normal agricultural and/or forestry activity, including but not limited to buildings or other structures, placement of manufactured homes, mining, dredging, filling, grading, paving, excavation or drilling operations or storage of equipment or materials, which materially affects the existing condition or use of any land or structure.
Elevation Certificate	FEMA Form 81-31, on which surveyed elevations and other data pertinent to a property and a building are identified and which shall be completed by a <i>licensed</i> professional land surveyor or a <i>licensed</i> professional engineer, as specified by the Floodplain Administrator. When used to document the height above grade of buildings in <i>special flood hazard areas</i> for which <i>base flood elevation</i> data are not available, the Elevation Certificate shall be completed in accordance with the instructions issued by FEMA. [Note: FEMA Form 81-31 and instructions are available online at http://www.fema.gov/library/viewRecord.do?id=1383 .]
Enclosure Below the Lowest Floor	An unfinished or <i>flood-resistant</i> enclosure that is located below an elevated building, is surrounded by walls on all sides, and is usable solely for parking of vehicles, building access or storage, in an area other than a <i>basement</i> area, provided that such enclosure is built in accordance with the applicable design requirements specified in these regulations. Also see "Lowest Floor."
Federal Emergency Management Agency (FEMA)	The Federal agency with the overall responsibility for administering the National Flood Insurance Program.
Flood or Flooding	A general and temporary condition of partial or complete inundation of normally dry land areas from: <ul style="list-style-type: none"> (1) The overflow of inland or tidal waters, and/or (2) The unusual and rapid accumulation or runoff of surface waters from any source.

<u>Term</u>	<u>Definition</u>
Flood, One-Hundred Year	<u>See: One-Hundred Year Flood</u>
Floodplain, One-Hundred Year	<u>See: One-Hundred Year Floodplain</u>
Flood Damage-Resistant Materials	Any construction material that is capable of withstanding direct and prolonged contact with floodwaters without sustaining any damage that requires more than cosmetic repair. [Note: See NFIP Technical Bulletin #2, "Flood Damage-Resistant Materials Requirements."]
Flood Insurance Rate Map (FIRM)	An official map on which the Federal Emergency Management Agency has delineated <i>special flood hazard areas</i> to indicate the magnitude and nature of <i>flood hazards</i> , to designate applicable flood zones, and to delineate floodways, if applicable. FIRMs that have been prepared in digital format or converted to digital format are referred to as Digital FIRMs (DFIRM).
Flood Insurance Study (FIS)	The official report in which the Federal Emergency Management Agency has provided <i>flood profiles</i> , <i>floodway</i> information, and the water surface elevations.
Flood Opening	A flood opening (non-engineered) is an opening that is used to meet the prescriptive requirement of 1 square inch of net open area for every square foot of enclosed area. An engineered flood opening is an opening that is designed and certified by a <i>licensed</i> professional engineer or <i>licensed</i> architect as meeting certain performance characteristics, including providing automatic entry and exit of floodwaters; the certification requirement may be satisfied by an individual certification or issuance of an Evaluation Report by the ICC Evaluation Service, Inc. [Note: See NFIP Technical Bulletin #1, "Openings in Foundation Walls and Walls of Enclosures."]
Flood Protection Elevation	The <i>base flood elevation</i> plus two (2) feet of freeboard, except for Solomons Town Center where the Flood Protection Elevation is 10' NAVD 88. Freeboard is a factor of safety that compensates for uncertainty in factors that could contribute to <i>flood</i> heights greater than the height calculated for a selected size <i>flood</i> and <i>floodway</i> conditions, such as wave action, obstructed bridge openings, debris and ice jams, climate change, and the hydrologic effect of urbanization in a watershed.

<u>Term</u>	<u>Definition</u>
Flood Zone	<p>A designation for areas that are shown on <i>Flood Insurance Rate Maps</i>:</p> <ol style="list-style-type: none"> (1) Zone A: <i>Special flood hazard areas</i> subject to inundation by the 1-percent annual chance (100-year) <i>flood</i>; <i>base flood elevations</i> are not determined. (2) Zone AE and Zone A1-30: <i>Special flood hazard areas</i> subject to inundation by the 1-percent annual chance (100-year) <i>flood</i>; <i>base flood elevations</i> are determined; <i>floodways</i> may or may not be determined. In areas subject to tidal <i>flooding</i>, the Limit of Moderate Wave Action may or may not be delineated. (3) Zone AH and Zone AO: <i>Areas of shallow flooding</i>, with <i>flood</i> depths of 1 to 3 feet (usually areas of ponding or sheet flow on sloping terrain), with or without BFEs or designated <i>flood</i> depths. (4) Zone B and Zone X (shaded): Areas subject to inundation by the 0.2-percent annual chance (500-year) <i>flood</i>; areas subject to the 1-percent annual chance (100-year) <i>flood</i> with average depths of less than 1 foot or with contributing drainage area less than 1 square mile; and areas protected from the <i>base flood</i> by levees. (5) Zone C and Zone X (unshaded): Areas outside of Zones designated A, AE, A1-30, AO, VE, V1-30, B, and X (shaded). (6) Zone VE and Zone V1-30: <i>Special flood hazard areas</i> subject to inundation by the 1-percent annual chance (100-year) <i>flood</i> and subject to high velocity wave action (also see <i>coastal high hazard area</i>).
Floodplain	Any land area susceptible to being inundated by water from any source (see definition of "Flood" or "Flooding").

1700-3019211

<u>Term</u>	<u>Definition</u>
Floodproofing or Floodproofed	Any combination of structural and nonstructural additions, changes, or adjustments to buildings or <i>structures</i> which reduce or eliminate <i>flood</i> damage to real estate or improved real property, water and sanitary facilities, <i>structures</i> and their contents, such that the buildings or <i>structures</i> are watertight with walls substantially impermeable to the passage of water and with structural components having the capability of resisting hydrostatic and hydrodynamic loads and effects of buoyancy. [Note: State regulations at COMAR 26.17.11(B)(7) do not allow new nonresidential buildings in <i>nontidal waters of the State</i> to be floodproofed.]
Floodproofing Certificate	FEMA Form 81-65 that is to be completed, signed and sealed by a <i>licensed</i> professional engineer or <i>licensed</i> architect to certify that the design of <i>floodproofing</i> and proposed methods of construction are in accordance with the applicable requirements of Section 5.6(B) of these regulations. [Note: FEMA Form 81-65 is available online at http://www.fema.gov/library/viewRecord.do?id=1600 .]
Floodway	The channel of a river or other <i>watercourse</i> and the adjacent land areas that must be reserved in order to pass the <i>base flood</i> discharge such that the cumulative increase in the water surface elevation of the <i>base flood</i> discharge is no more than a designated height. When shown on a <i>FIRM</i> , the floodway is referred to as the "designated floodway."
Freeboard	An increment of elevation added to the base flood elevation to provide a factor of safety for uncertainties in calculations, wave actions, subsidence, or other unpredictable effects.
Free-of-Obstruction	A term that describes open foundations (pilings, columns, or piers) without attached elements or foundation components that would obstruct the free passage of floodwaters and waves beneath <i>structures</i> that are elevated on such foundations. [Note: See NFIP Technical Bulletin #5, "Free-of-Obstruction Requirements."]
Functionally Dependent Use	A use which cannot perform its intended purpose unless it is located or carried out in close proximity to water; the term includes only docking facilities, port facilities that are necessary for the loading and unloading of cargo or passengers, and ship building and ship repair facilities, but does not include long-term storage or related manufacturing facilities.

<u>Term</u>	<u>Definition</u>
Highest Adjacent Grade	The highest natural elevation of the ground surface, prior to construction, next to the proposed foundation of a <i>structure</i> .
Historic Feature	<p>Any object or structure having a special historical, architectural, cultural or aesthetic value for a community that is:</p> <ol style="list-style-type: none"> (1) Individually listed in the National Register of Historic Places (a listing maintained by the U.S. Department of Interior) or preliminarily determined by the Secretary of the Interior as meeting the requirements for individual listings on the National Register; (2) Certified or preliminarily determined by the Secretary of the Interior as contributing to the historical significance of a registered historic district or a district preliminarily determined by the Secretary to qualify as a registered historic district; (3) Individually listed on the Maryland Inventory of Historic Properties or Archeological Sites Inventory maintained by the Maryland Historical Trust; or (4) Individually listed on the inventory of historic places maintained by Calvert County whose historic preservation program has been certified by the Maryland Historical Trust or the Secretary of the Interior.
Hydrologic and Hydraulic Engineering Analyses	Analyses performed by a <i>licensed</i> professional engineer, in accordance with standard engineering practices that are accepted by the Maryland Department of the Environment (Nontidal Wetlands & Waterways) and FEMA, used to determine the <i>base flood</i> , other frequency floods, <i>flood</i> elevations, <i>floodway</i> information and boundaries, and <i>flood</i> profiles.

<u>Term</u>	<u>Definition</u>
Letter of Map Change (LOMC)	<p>A Letter of Map Change is an official FEMA determination, by letter, that amends or revises an effective <i>Flood Insurance Rate Map</i> or <i>Flood Insurance Study</i>. Letters of Map Change include:</p> <p>Letter of Map Amendment (LOMA): An amendment based on technical data showing that a property was incorrectly included in a designated <i>special flood hazard area</i>. A LOMA amends the current effective <i>Flood Insurance Rate Map</i> and establishes that a specific property or <i>structure</i> is not located in a <i>special flood hazard area</i>.</p> <p>Letter of Map Revision (LOMR): A revision based on technical data that may show changes to <i>flood zones</i>, <i>flood elevations</i>, <i>floodplain</i> and <i>floodway</i> delineations, and planimetric features. A Letter of Map Revision Based on Fill (LOMR-F), is a determination that a <i>structure</i> or parcel of land has been elevated by fill above the <i>base flood elevation</i> and is, therefore, no longer exposed to <i>flooding</i> associated with the <i>base flood</i>. In order to qualify for this determination, the fill must have been permitted and placed in accordance with the <i>community's</i> floodplain management regulations.</p> <p>Conditional Letter of Map Revision (CLOMR): A formal review and comment as to whether a proposed <i>flood</i> protection project or other project complies with the minimum NFIP requirements for such projects with respect to delineation of <i>special flood hazard areas</i>. A CLOMR does not revise the effective <i>Flood Insurance Rate Map</i> or <i>Flood Insurance Study</i>; upon submission and approval of certified as-built documentation, a Letter of Map Revision may be issued by FEMA, to revise the effective <i>FIRM</i>.</p>
Licensed	As used in these regulations, licensed refers to professionals who are authorized to practice in the State of Maryland by issuance of licenses by the Maryland Board of Architects, Maryland Board of Professional Engineers, Maryland Board of Professional Land Surveyors, and the Maryland Real Estate Appraisers and Home Inspectors Commission.

<u>Term</u>	<u>Definition</u>
Lowest Floor	The lowest floor of the lowest enclosed area (including <i>basement</i>) of a building or <i>structure</i> ; the floor of an <i>enclosure below the lowest floor</i> is not the lowest floor provided the enclosure is constructed in accordance with these regulations. The lowest floor of a <i>manufactured home</i> is the bottom of the lowest horizontal supporting member (longitudinal chassis frame beam).
Manufactured Home	A structure, transportable in one or more sections and designed to be used as a dwelling, which is built on a permanent chassis and is designed for use with or without a permanent foundation when connected to the required utilities. The structure is built in a factory and bears a seal certifying that it conforms to the U.S. Department of Housing and Urban Development's (HUD) Manufactured Home Construction and Safety Standards Code (a.k.a. mobile home or residential trailer). This definition does not include modular houses or recreational vehicles.
Market Value	The price at which a property will change hands between a willing buyer and a willing seller, neither party being under compulsion to buy or sell and both having reasonable knowledge of relevant facts. For the purposes of these regulations, the market value of a building is determined by a <i>licensed</i> real estate appraiser or the most recent, full phased-in assessment value of the building (improvement) determined by the Maryland Department of Assessments and Taxation.
Maryland Department of the Environment (MDE)	A principal department of the State of Maryland that is charged with, among other responsibilities, the coordination of the National Flood Insurance Program in Maryland (NFIP State Coordinator) and the administration of regulatory programs for <i>development</i> and construction that occur within the <i>waters of the State</i> , including nontidal wetlands, nontidal waters and floodplains, and State and private tidal wetlands (Tidal Wetlands). Unless otherwise specified, "MDE" refers to the Department's Wetlands and Waterways Program.
National Flood Insurance Program (NFIP)	The program authorized by the U.S. Congress in 42 U.S.C. §§4001 - 4128. The NFIP makes flood insurance coverage available in communities that agree to adopt and enforce minimum regulatory requirements for <i>development</i> in areas prone to <i>flooding</i> (see definition of "Special Flood Hazard Area").

<u>Term</u>	<u>Definition</u>
New Construction	<i>Structures</i> , including additions and improvements, and the placement of <i>manufactured homes</i> , for which the <i>start of construction</i> commenced on or after September 268, 1984, the initial effective date of the Calvert County <i>Flood Insurance Rate Map</i> , including any subsequent improvements, alterations, modifications, and additions to such <i>structures</i> .
NFIP State Coordinator	<u>See Maryland Department of the Environment.</u>
Nontidal Waters of the State	See "Waters of the State." As used in these regulations, "nontidal waters of the State" refers to any stream or body of water within the State that is subject to State regulation, including the "100-year frequency <i>floodplain of free-flowing waters</i> ." COMAR 26.17.04 states that "the landward boundaries of any tidal waters shall be deemed coterminous with the wetlands boundary maps adopted pursuant to Environment Article, §16-301, Annotated Code of Maryland. Therefore, the boundary between the tidal and nontidal waters of the State is the tidal wetlands boundary.
Person	An individual or group of individuals, receiver, trustee, guardian, executor, administrator, fiduciary, or representative of any kind, or any partnership, firm, association, public or private corporation, or any of their affiliates, or any other entity, including state and local governments and agencies.
Recreational Vehicle	A vehicle that is built on a single chassis, 400 square feet or less when measured at the largest horizontal projection, designed to be self-propelled or permanently towable by a light duty truck, and designed primarily not for use as a permanent dwelling, but as temporary living quarters for recreational, camping, travel, or seasonal use. These vehicles include but are not limited to travel trailers, truck campers, camping trailers and self-propelled motor homes.
Special Flood Hazard Area (SFHA)	The land in the <i>floodplain</i> subject to a one-percent or greater chance of <i>flooding</i> in any given year. Special flood hazard areas are designated by the Federal Emergency Management Agency in <i>Flood Insurance Studies</i> and on <i>Flood Insurance Rate Maps</i> as Zones A, AE, AH, AO, A1-30, and A99, and Zones VE and V1-30. The term includes areas shown on other flood maps that are specifically listed or otherwise described in Section 1.5.

<u>Term</u>	<u>Definition</u>
Start of Construction	The date the building permit was issued, provided the actual start of construction, repair, reconstruction, rehabilitation, addition placement, or other improvement was within 180 days of the permit date. The actual start means either the first placement of permanent construction of a <i>structure</i> on a site, such as the pouring of slab or footings, the installation of piles, the construction of columns, or any work beyond the stage of excavation; or the actual placement of a <i>manufactured home</i> on a foundation. Permanent construction does not include land preparation, such as clearing, grading and filling; nor does it include the installation of streets and/or walkways; nor does it include excavation for a <i>basement</i> , footings, piers, or foundations or the erection of temporary forms; nor does it include the installation on the property of <i>accessory structures</i> , such as garages or sheds not occupied as dwelling units or not part of the main <i>structure</i> . For <i>substantial improvements</i> , the actual start of construction is means the first alteration of any wall, ceiling, floor, or other structural part of a building, whether or not that alteration affects the external dimensions of the building.
Structure	A combination of building materials that are purposely joined together on, above or below the surface of the land or water including those that do not result in lot coverage, including a gas or liquid storage tank that is principally above ground, as well as a <i>manufactured home</i> .
Substantial Construction	A building shall be considered to have substantial construction if over 50 percent of the square footage is under roof and enclosed.
Substantial Damage	Damage of any origin sustained by a building or <i>structure</i> whereby the cost of restoring the building or <i>structure</i> to its before damaged condition would equal or exceed 50 percent of the <i>market value</i> of the building or <i>structure</i> before the damage occurred. Also used as "substantially damaged" structures.

<u>Term</u>	<u>Definition</u>
Substantial Improvement	<p>Any reconstruction, rehabilitation, addition, or other improvement of a building or <i>structure</i>, the cost of which equals or exceeds 50 percent of the <i>market value</i> of the building or <i>structure</i> before the <i>start of construction</i> of the improvement. The term includes <i>structures</i> which have incurred <i>substantial damage</i>, regardless of the actual repair work performed. The term does not, however, include either:</p> <ul style="list-style-type: none"> (1) Any project for improvement of a building or <i>structure</i> to correct existing violations of State or local health, sanitary, or safety code specifications which have been identified by the local code enforcement official prior to submission of an application for a permit and which are the minimum necessary to assure safe living conditions; or (2) Any alteration of a <i>historic structurefeature</i>, provided that the alteration will not preclude the <i>structure's</i> continued designation as a <i>historic structurefeature</i>.
Temporary Structure Incidental to Sales or Rentals in New Residential or Commercial Developments (sales trailers)	<p>A structure with an impermanent foundation used by a construction contractor, realtor, or other development professional as an office during construction of a subdivision or development. To be considered temporary in a special flood hazard area, the structure must be removed within 180 days of its installation, use or erection.</p>
Temporary Structure Incidental to Schools (Classroom Relocatables)	<p>A structure containing one or more rooms, each of which is designed, intended, and equipped for use as a place for formal instruction of pupils by a teacher in a school, not constructed with a permanent foundation and which shall not remain permanently on the site. To be considered temporary in a special flood hazard area, the structure must be removed within 180 days of its installation, use or erection.</p>
Violation, Floodplain	<p>Any construction or <i>development</i> in a <i>special flood hazard area</i> that is being performed without an issued permit. The failure of a building, <i>structure</i>, or other <i>development</i> for which a permit is issued to be fully compliant with these regulations and the conditions of the issued permit. A building, <i>structure</i>, or other <i>development</i> without the required design certifications, the <i>Elevation Certificate</i>, or other evidence of compliance required is presumed to be a <i>violation</i> until such time as the required documentation is provided.</p>

<u>Term</u>	<u>Definition</u>
Waters of the State	<p>[See Environment Article, Title 5, Subtitle 1, Annotated Code of Maryland.] Waters of the State include:</p> <ul style="list-style-type: none">(1) Both surface and underground waters within the boundaries of the State subject to its jurisdiction;(2) That portion of the Atlantic Ocean within the boundaries of the State;(3) The Chesapeake Bay and its tributaries;(4) All ponds, lakes, rivers, streams, public ditches, tax ditches, and public drainage systems within the State, other than those designed and used to collect, convey, or dispose of sanitary sewage; and(5) The <i>floodplain</i> of free-flowing waters determined by MDE on the basis of the 100-year <i>flood</i> frequency.

